

Universal drilling/milling machine with automatic table feed for X and Y axis

Facts that impress in terms of quality, performance and price

- ▶ Vibration absorbing cast design
- ▶ Operation-friendly control panel
- ▶ LED lamp
- ▶ Milling head pivots through 45° to left and right
- ▶ Automatic feed of X and Y axis with speed adjustment
- ▶ Automatic and adjustable limit switch cut-off of the X axis
- ▶ Mechanical spindle sleeve feed for drilling via spindle sleeve lever
- ▶ Gears in oil bath with polished, hardened gear wheels
- ▶ Right-handed/left-handed rotation
- ▶ Coupling for switching from manual coarse feed to manual fine feed
- ▶ Large Y axis spindle head holder throat of 250 - 650 mm
- ▶ Precision Cross table, generously dimensioned with precision surface finish with adjustable V-ledges
- ▶ Height-adjustable protective screen with microswitch for best possible user protection against chips and parts being flung out
- ▶ Solid and generously dimensioned cross table with dovetails, precision surface finish including T-slots and adjustable cleats, tilting $\pm 45^\circ$
- ▶ Coolant system




Fig.: MT 50E

Technical specifications, accessories and dimensions

Model	MT 50E
Article no.	3336010
Technical data	
Electrical connection	400 V / 3 Ph ~ 50 Hz
Drive motor	0.85 / 1.5 kW
Coolant pump motor	40 W
Drilling performance	
Drilling performance in steel (S235JR)	Ø 30 mm
Continuous drilling performance in steel (S235JR)	Ø 25 mm
Max. sensor head size	Ø 63 mm
Max. shaft milling cutter size	Ø 25 mm
Spindle	
Spindle seat	SK40 DIN 2080
Spindle sleeve stroke	120 mm
Draw-in rod	M16
Distance spindle to cross table	60 - 360 mm
Drilling/milling head	
Spindle speeds	115 - 1 750 rpm
Gears / motor speeds	4-speed / 2-speed
Milling head tilt	± 45°
Throat	250 - 650 mm
Cross table	
Length x width	1 000 x 240 mm
Cross table max. load bearing capacity	150 kg
T-slot size / quantity	14 mm / 4
Swivel range	± 45°
Travel	
X axis	manual 580 mm / automatic 500 mm
Y axis	manual 230 mm / automatic 150 mm
Z axis manual	400 mm
Dimensions	
Length x width x height	1 360 x 1 150 x 2 080 mm
Weight	760 kg

Accessories	Article no.
Parallel shim set, 20-part	3354001
Horizontal-vertical rotary indexing table RT 150	3356150
Horizontal-vertical rotary indexing table RT 200	3356200
Horizontal-vertical rotary indexing table RTE 165	3356365
Horizontal-vertical rotary indexing table RTU 165	3354165
Assortment of clamping tools size 12, 58 parts	3352017
End mill set HSS TiN-coated 12-part	3352250
End mill set HSS TiN-coated 20-part	3352255
Workpiece support WPS-4	3354264
Precision machine shoe SEU1 (4 pcs. required) see page 132	3352985
Levelling platen SE 85 (4 pcs. required)	3352982
Arbor for drill chuck ISO 40/B16	3352070
Collet chuck set 18-part ISO40	3352056
Copying and facing blade head ISO 40 DIN 2080	3350216
Precision bore head set ISO 40	3352128
Hold-down unit set of 2	3352031



Scope of supply

- › Key type drill chuck 3 - 16 mm / B18
- › Arbor for drill chuck ISO40 / B18
- › T-slot nuts
- › Push-out tool
- › Reduction sleeve ISO40- MT 3 and MT 3-MT 2
- › Operating tool

Machine vices	Article no.
FMS 125	3354125
FMSN 125	3354120
VMQ 100	3354181
MV3-75	3354175
DAS 100	3355500
ZAS 50	3354170